

EXCAVATOR MULCHERS

FML/EX



from 90 to 120 HP



Ø 20 cm max



from 14 to 20 t

FORESTRY MULCHER WITH SWINGING HAMMER ROTOR FOR EXCAVATORS.

The FML/EX mulcher has all the same attributes as the UML/EX but with a flail rotor. The enclosed hydraulic door opening and closing system creates a completely enclosed frame that protects the internal components from dust and debris.



STANDARD EQUIPMENT

Enclosed machine body
Belt transmission
Hydraulic piston motor 63cc with relief and anticavitation valve
Flow control valve
Hydraulic hood
Welded counter blade
Bolted dual row protection chains

Motor enclosed in frame
Motor integrated into the frame
Supporting service leg

OPTIONS

Diverter valve
Customized attachment bracket
Customized attachment bracket with fixed thumb



Customized attachment bracket

Hydraulic controlled hood
revolutionary system for door opening/closing that prevents dirt from entering into the service areas of the machine

Steel counter-blades
helps mulch material into a smaller final size

Motor enclosed in frame
protected from dirt and impact

MODEL	Power (HP)		Flow rate (L/min)		Pressure (bar)		Excavator weight (t.)		Working width (mm)	Weight (kg)	Max shredding diameter (mm)	No. hammers type FMM
	min	max	min	max	min	max	min	max				
FML/EX 100	90	120	110	150	220	350	14	20	1100	950	200	16
FML/EX 125	90	120	110	150	220	350	14	20	1340	1050	200	20
FML/EX 150	100	120	110	150	220	350	14	20	1580	1150	200	24

Data refers to machine as standard. The technical data in this catalog may be altered without prior notice.