

EXCAVATOR MULCHERS

FML/HY



from 70 to 110 HP



Ø15 cm max



from 7 to 14 t

FORESTRY MULCHER WITH SWINGING HAMMER ROTOR FOR EXCAVATORS.

The heavy duty construction and design elements integrated from our other mulchers make the FML/HY suitable for the most demanding applications. The updated positioning of hydraulic connections guarantee easy and rapid mounting. The hydraulic motor is internally positioned in the frame to protect it from dirt and potential damage, ensuring maximum reliability throughout the life of the attachment.



STANDARD EQUIPMENT

Enclosed machine body
Belt transmission
32/65cc variable manual displacement hydraulic piston motor with relief and anticavitation valve
Flow control system valve
Hydraulic hood
Welded counter blade
Protection chains
Motor enclosed in frame
Supporting service leg

OPTIONS

Hood with mechanical adjustment
Diverter valve
Customized attachment bracket
Customized attachment bracket with fixed thumb



Customized attachment bracket

Steel counter-blades helps mulch material into a smaller final size

Flow control valve to protect the motor from excessive flow

Forestry mulcher with swinging hammers rotor for excavators

MODEL	Power (HP)		Flow rate (L/min)		Pressure (bar)		Excavator weight (t.)		Working width (mm)	Weight (kg)	Max shredding diameter (mm)	No. hammers type FMM
	min	max	min	max	min	max	min	max				
FML/HY 100	70	110	70	160	180	250	7	14	1100	830	150	16
FML/HY 125	70	110	70	160	180	250	7	14	1340	930	150	20
FML/HY 150	70	110	70	160	180	250	7	14	1580	1030	150	24

Data refers to machine as standard. The technical data in this catalog may be altered without prior notice.