



from 70 to 150 HP



from 12 to 20 t

## DISC STUMP CUTTER FOR EXCAVATORS.

The SCM/EX/VT is designed to remove stumps quickly and easily. The front hood with hydraulic adjustment and front fixed thumb are designed to shift previously cut material. This feature combined with the reliability and resistance of the disc allows for the best performance and safety while the stumps are being removed.

### STANDARD EQUIPMENT

- Enclosed machine body
- Belt transmission
- 160/115cc variable torque hydraulic piston motor
- Flow control valve
- Hydraulic front hood
- Motor integrated into the frame
- Screwed protection chains
- Adjustable supporting service stand

### OPTIONS

- Customized setting hydraulic motor
- Diverter valve
- Customized attachment bracket
- Customized attachment bracket with fixed thumb
- Front fixed thumb



## FEATURES



Access panel



**VT motor**  
to increase performance and reduce operating costs


**Front hydraulic hood with bolt-on chains/ protection plates**

**Motor enclosed in frame**  
protected from dirt and damage


**Adjustable supporting service stand**  
for storing the machine when not in use



## MAIN OPTIONS



**1 Front fixed thumb**



**2 VT motor**  
Adjustable motor to obtain the maximum performance from any excavator



**3 Customized attachment bracket with fixed thumb**



**4 Customized attachment bracket**

MODEL	Power (HP)		Flow rate (L/min)		Pressure (bar)		Excavator weight (t.)		Diametro Rotore (mm)	Total width (mm)	Weight (kg)	No. teeth M1/M2/M3/M4
	min	max	min	max	min	max	min	max				
SCM/EX/VT	70	150	120	220	220	350	12	20	790	770	1020	12+3+12+3

Data refers to machine as standard. The technical data in this catalog may be altered without prior notice.