

MULTITASKS

SFM - SFM/HP



from 150 to 300 HP



Ø30 cm max (stones)
Ø40 cm max (trees)
Ø50 cm max (stump)



D30 cm

STONE CRUSHER, FORESTRY TILLER AND MULCHER WITH FIXED TOOTH ROTOR.

The SFM runs at two different speeds. As a mulcher it runs at 1000 rpm, as a stone crusher it runs at 540 rpm. This allows the SFM to mulch trees up to 40 cm diameter or grind rocks up to 30 cm diameter. Design elements from both our mulchers and tillers were used to create an attachment that is the perfect solution for small and large operations. All internal wear components are relatively easy to replace, making this machine desirable for anyone seeking a good long term investment.

STANDARD EQUIPMENT	
Friction clutch on side PTO	Hydraulic top link
PTO shaft with cam clutch	Z style self ranging system of the PTO drive shaft/gearbox
Gearbox with freewheel	Hydraulic hoses integrated in the frame
Transmission with side gearbox	Cylinder protection
Side gearbox with oil cooling system (SFM 200, 225 and 250 and SFM HP 200 and 225)	Inside lateral protections
Hydraulic hood	Dual row protection chains
Forged and hardened interchangeable counter-blades	
Adjustable Hardox® counter-blade	
Interchangeable inner antiwear plates in Hardox®	
Adjustable extended 3 point linkage	
Enclosed machine body	

OPTIONS
Hydraulically adjustable skids
W style self aligning device between PTO drive shaft/gearbox
Hydraulic push frame
Grader blade (not compatible with roller)
Hydraulic controlled roller (not compatible with dozing blade)



THE LEADER OF MULTITASK

FEATURES

Z style self ranging system of the PTO drive shaft/gearbox helps keep the correct operating angle between the PTO shaft and the power take-off

Hydraulically controlled rear door adjust final product size while machine is working

Forged and hardened interchangeable counter-blades for longest working life

Adjustable extended 3 point linkage fits perfectly with any kind of tractor

Transmission with side gearbox reduces rotor speed while maintaining power

MAIN OPTIONS

1 W style self aligning device between PTO drive shaft/gearbox allows the machine to work at several angles without damaging the PTO

2 Hydraulic controlled roller helps with compaction and working uneven terrain

MODEL	Power (HP)		PTO (rpm)	Working width (mm)	Total width (mm)	Weight (kg)	Max shredding diameter (mm)			Max working depth (mm)	No. teeth type F/3 + STC/3/FP
	min	max					Stones	Trees	Stump		
SFM 175	150	250	540 - 1000*	1815	2295	3100	300	400	500	300	48+2
SFM 200	160	250	540 - 1000*	2055	2535	3400	300	400	500	300	52+2
SFM 225	170	250	540 - 1000*	2295	2775	3700	300	400	500	300	60+2
SFM 250	180	250	540 - 1000*	2535	3015	4000	300	400	500	300	64+2
SFM/HP 225	170	300	1000**	2295	2775	3750	300	400	500	300	60+2
SFM/HP 250	180	300	1000**	2535	3015	4050	300	400	500	300	64+2

Data refers to machine as standard. The technical data in this catalog may be altered without prior notice.

*540 rpm as stone crusher - 1000 rpm as forestry mulcher
**1000 rpm for stone crushing, tilling and mulching