



from 50 to 110 HP



Ø20 cm max

FORESTRY MULCHER WITH FIXED TOOTH ROTOR (UML/ST) OR WITH FLAIL ROTOR (FML/ST).

This forestry mulcher was designed and built for use with low horsepower tractors. It is rated for bushes, crop residue, and trees up to 25 (max diameter).

The UML/ST is a compact, heavy duty mulcher with high productivity.



STANDARD EQUIPMENT
PTO shaft (FML/ST)
PTO shaft with cam clutch (UML/ST)
Gearbox with freewheel
Trasmission with belts in XPB
Rear hood
Welded steel counter-blades
Adjustable skids
Protection chains

OPTIONS
Possibility to choose Transmission 540 / 1000 rpm
Frontal attachment
Extended 3 point linkage
Hydraulic top link
Mechanical push frame
Special skids to go underground (UML/ST)
Different teeth (UML/ST)



Mechanical push frame
(optional)

Reversible attachment
(optional)

Rotor with swinging (FMM for FML/ST) or fixed (C/3 for UML/ST) hammers

Choice between 540 rpm and 1000 rpm transmission

MODEL	Power (HP)		PTO (rpm)	Working width (mm)	Total width (mm)	Weight (kg)	Max shredding diameter (mm)	No. teeth type C/3 + C/3/SS	No. teeth type I + C/3/SS	No. teeth type FMM
	min	max								
UML/ST 125	50	110	540 o 1000	1340	1630	840	200	26+2	36+2	/
UML/ST 150	60	110	540 o 1000	1580	1840	900	200	32+2	42+2	/
UML/ST 175	70	110	540 o 1000	1820	2080	970	200	36+2	50+2	/
UML/ST 200	80	110	540 o 1000	2060	2380	1040	200	42+2	58+2	
FML/ST 125	50	100	540 o 1000	1340	1630	820	200	/	/	20
FML/ST 150	60	110	540 o 1000	1580	1840	890	200	/	/	24
FML/ST 175	70	110	540 o 1000	1820	2080	950	200	/	/	28
FML/ST 200	80	110	540 o 1000	2060	2380	1020	200	/	/	32

Data refers to machine as standard. The technical data in this catalog may be altered without prior notice.