



from 180 to 350 HP



Ø 35 cm max

FORESTRY MULCHER WITH FIXED TOOTH ROTOR.

The UMM is a robust mulcher with high productivity and light weight. Equipped with a fixed tooth rotor, the UMM is a very versatile mulcher capable of running on tractors from 180 HP to 350 HP. It is rated to mulch trees up to 35 cm diameter. Our auto aligning PTO system helps ensure an optimum working position.

STANDARD EQUIPMENT	
PTO shaft with cam clutch	Z style self ranging system of the PTO drive shaft/gearbox
Gearbox with freewheel	Cylinder protection
Transmission with belts in Poly-V Kevlar	Stronger HP transmission for tractors up to 450 HP
Hydraulic hood	Dual row protection chains
Forged and hardened interchangeable counter-blades	Protection plates for bolt-on chains
Three rows of forged and hardened interchangeable counter-blades	
Inner anti wear clad plates FCP	
Adjustable skids	
Adjustable extended 3 point linkage	
Enclosed machine body	
Centralized greasing hub	
Hydraulic top link	
Hydraulic hoses integrated in the frame	

OPTIONS	
W style self aligning device between PTO drive shaft/gearbox	
Mechanical push frame	
Hydraulic push frame	
Extra ripper for push frame	
Hydraulic clutch transmission (UMM/S/HP 225 and 250)	
Special skids to go underground	
Multiple tooth options	



FEATURES

Cylinder protection to prevent cylinder damage

Reinforced hood helps to provide a finer product

Aggressive body design the protruding rotor allows more material to process without dragging

Inner anti wear clad plates FCP absorbs wear while protecting the frame

Three rows of forged and hardened interchangeable counter-blades for the longest working life while providing a finer product

Z style self ranging system of the PTO drive shaft/gearbox always keeps the correct operating angle between the PTO shaft and the power take-off

Bigger transmission for tractors with power up to 350 HP

Adjustable extended 3 point linkage fits perfectly with any kind of tractor

MAIN OPTIONS

- W style self aligning device between PTO drive shaft/gearbox** allows the mulcher to work at several angles without damaging the PTO
- Mechanical/hydraulic push frame** guides and pushes material away from carrier
- Additional ripper for push frame** helps with the positioning of standing material while mulching
- Standard hydraulic clutch transmission** protects the transmission at PTO engagement for smooth starting and improves machine performance

MODEL	Power (HP)		PTO (rpm)	Working width (mm)	Total width (mm)	Weight including rotor (kg)		Max shredding diameter (mm)	No. teeth type	
	min	max				tipo C/3	tipo B/3		B/3+C/3/SS	C/3+C/3/SS
UMM/S 200	180	280	1000	2060	2490	2940	3250	350	72+2	44+2
UMM/S 225	190	280	1000	2300	2730	3070	3360	350	80+2	50+2
UMM/S 250	200	280	1000	2540	2970	3210	3520	350	92+2	56+2
UMM/S/HP 200	180	350	1000	2060	2490	2980	3280	350	72+2	44+2
UMM/S/HP 225	190	350	1000	2300	2730	3310	3580	350	80+2	50+2
UMM/S/HP 250	200	350	1000	2540	2970	3450	3870	350	92+2	56+2

Data refers to machine as standard. The technical data in this catalog may be altered without prior notice.